

# Single Port VDSL2 Line Driver with Shutdown

# AD8398A

### **FEATURES**

Voltage feedback Wide output swing 18.4 V p-p differential,  $R_{LOAD} = 20 \Omega$  from 12 V supply High output current Linear output current of 450 mA peak Low distortion -65 dBc for Profile 8b @ 20.4 dBm -55 dBc for Profile 17a @ 14.5 dBm High speed 85 MHz bandwidth (Av DIFF = 5)

### **APPLICATIONS**

ADSL2+/VDSL2 CO/CPE line driver PLC line driver Consumer xDSL modems Twisted pair line drivers

### FUNCTIONAL BLOCK DIAGRAM



Figure 1. Thermally Enhanced, 4 mm × 4 mm, 16-Lead LFCSP\_WQ

### **TYPICAL APPLICATION DIAGRAM**



### GENERAL DESCRIPTION

The AD8398A comprises two high-speed voltage feedback operational amplifiers. When configured as a differential line driver, the AD8398A is an ideal choice for ADSL2+, VDSL2, and power line communications (PLC) applications. It has high output current, high bandwidth, and fast slew rate, combined with exceptional MTPR and common-mode stability. The AD8398A is available in a thermally enhanced 4 mm × 4 mm, 16-lead LFCSP.

The AD8398A incorporates power management functionality via two CMOS-compatible control pins, PD0 and PD1. These pins select one of four operating modes: full power, medium power, low power, or complete power-down. In the power-down mode, the quiescent current drops to 0.7 mA.

The AD8398A operates in the extended industrial temperature range of  $-40^{\circ}$ C to  $+85^{\circ}$ C.

For more information about the AD8398A, email: broadbandproducts@analog.com.

Rev. Sp0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

 One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.

 Tel: 781.329.4700
 www.analog.com

 Fax: 781.461.3113
 ©2008 Analog Devices, Inc. All rights reserved.

## AD8398A

## NOTES

©2008 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners. D07760F-0-11/08(Sp0)



www.analog.com

Rev. Sp0 | Page 2 of 2